

## tesa® 4330

High performance paper masking tape for paintworks with oven drying up to 140 °C

tesa® 4330 is a finely crêped, flexible, wet resistant masking tape with a high tensile strength.

### Main Application

Further applications are e.g.

- masking of circuit boards before plating
- cable bundling
- packaging

### Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	12 %
▪ Total thickness	175 µm	▪ Tensile strength	42 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	140 °C
▪ Adhesion to steel	4.8 N/cm		

### Properties

▪ Hand tearability	●●●●	▪ Sharp colour edge	●●●
▪ Easy to remove	yes	▪ Conformability	●●●
▪ Paint anchorage	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

### Additional Information

This tape guarantees sharp edged finishing due to its fine creped structure. The adhesion of paint and filler to the reverse side of the tape is excellent.

tesa® 4330 can be removed very easily without tearing or leaving any residues.

tesa® 4330 is also available for converting/die-cutting with a paper liner (4330 PV1).

For latest information on this product please visit <http://l.tesa.com/?ip=04330>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.